



### G-Tek® PolyKor® Seamless Knit PolyKor® Blended Glove with Polyurethane Coated Flat Grip on Palm & Fingers

- Seamless construction offers increased comfort and breathability
- PolyKor® blended shell is lightweight and provides excellent dexterity, tactile sensitivity, and cut resistance
- Polyurethane coatings take on the surface properties of the glove liner providing a tactile grip in dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Knit wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- Washable, resistant to chemicals, water, and ultraviolet light

### Applications

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging



### Technical Data

|                      |                       |
|----------------------|-----------------------|
| Color                | Blue                  |
| Sizes Available      | --                    |
| Packaging            | Bulk Pack             |
| Packed               | --                    |
| Case Dimensions (cm) | 24.00 x 17.00 x 44.00 |
| Case Weight (kg)     | 3.00                  |
| Country of Origin    | China                 |
| Liner Material       | PolyKor               |
| Coating              | Polyurethane          |
| Coating Color        | Blue                  |
| Coating Coverage     | Palm & Fingers        |
| Grip                 | Flat                  |
| Gauge                | 18                    |
| Cuff                 | Knit Wrist            |
| Impact Protection    | --                    |
| Construction         | Coated Seamless Knit  |
| Certifications       | --                    |
| Product Circularity  | --                    |

### Performance Data

|                                 |        |
|---------------------------------|--------|
| Cut Level                       | A2     |
| ANSI Abrasion Level             | --     |
| ANSI Puncture Level             | 3      |
| ANSI Impact Level               | --     |
| ANSI Contact Heat Level         | --     |
| EN 388                          | 4342BX |
| ASTM F1358 Vertical Flame Level | --     |
| EN 407                          | --     |