



Technical Data

Color	Black
Sizes Available	S-XL
Packaging	Case
Packed	1/Case
Case Dimensions (cm)	43.18 x 20.32 x 12.70
Case Weight (kg)	1.13
Country of Origin	Japan
Polymer	Polyurethane
Grip	Smooth
Cuff	Straight
Length	12"
Powder	Powder Free
Thickness	4 Mil
Construction	Unsupported, ESD Safe
Certifications	TAA Compliant
Product Circularity	Recycled via Terracycle

QRP® PolyTuff®

Polyurethane Electrostatic Dissipative (ESD) Glove - 4 mil

- Packaged for ISO 5 (Class 100) applications
- Tough, sheer PolyTuff polyurethane (1.5 mil) film affords a high degree of tactile sensitivity
- Tough solvent process polyurethane, sulfur-free, no carbon shedding
- Ergonomic Comfort Curve hand specific design
- Static dissipative 10(6) ohms
- For use with Class I and Class II static sensitive devices
- ESD safe compliance to ANSI/ESD S20.20-2014
- Compliant with ASTM and IEST-RP-CC005.3 standards
- RoHS Compliant

Performance Data

ISO Cleanroom	ISO 5 (Class 100)
Temperature Resistant	--
Static Control Property	Static Dissipative

KEY: Made from recycled or bio-based Launderable Recyclable via TerraCycle®

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-06-28