

# SPECIFICATION SHEET

**STYLE: 556** 



## G-Tek® PolyKor®

Seamless Knit PolyKor® Blended Glove with Polyurethane Coated Smooth Grip on Palm & Fingers - 18 Gauge - Touchscreen

- Polyurethane coatings take on the surface properties of the glove liner providing a tactile grip in dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Polyurethane coating feels soft and flexible to maintain dexterity, and grips well without feeling sticky or tacky
- Reinforced thumb crotch provides longer wear life and increased protection
- Touchscreen compatible to allow the user to operate a touchscreen phone or device without removing gloves
- Knit wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification

# **Applications**

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging









## **Technical Data**

| Color                | Gray  |
|----------------------|---|
| Sizes Available      | XS-2XL  |
| Packaging            | Pair Bagged Retail Ready  |
| Packed               | 144/Case  |
| Case Dimensions (cm) | 56.00 x 28.00 x 36.00   |
| Case Weight (kg)     | 7.50  |
| Country of Origin    | China   |
| Liner Material       | PolyKor   |
| Coating              | Polyurethane  |
| Coating Color        | Black   |
| Coating Coverage     | Palm & Fingers  |
| Grip                 | Smooth  |
| Gauge                | 18  |
| Cuff                 | Knit Wrist  |
| Impact Protection    |   |
| Construction         | Coated Seamless Knit,<br>Reinforced Thumb Crotch,<br>Touchscreen Compatible |
| Certifications       |   |
| Product Circularity  | Recycled via Terracycle<br>Reusable / Launderable                           |

### **Performance Data**

| Cut Level                       | A5     |
|---------------------------------|--------|
| ANSI Abrasion Level             | 3      |
| ANSI Puncture Level             | 2      |
| ANSI Impact Level               |        |
| ANSI Contact Heat Level         |        |
| EN 388                          | 4X31EX |
| ASTM F1358 Vertical Flame Level |        |
| EN 407                          |        |

### **Care Instructions**













KEY: Made from recycled or bio-based Launderable & Recyclable via TerraCycle®