

# SPECIFICATION SHEET

STYLE: 44-305



### MaxiCut® Oil

Seamless Knit Engineered Yarn Glove with Nitrile Coated MicroFoam Grip on Palm, Fingers & Knuckles

- Micro-Foam nitrile coatings are compatible with light oils and will provide a good grip and excellent abrasion resistance
- Unique high performance yarns and fibers that offer cut protection while maintaining high levels of comfort
- Reinforcement between the thumb and forefinger
- Patented micro-foam nitrile coating offers 360° breathability making it the most breathable cut resistant glove on the market
- The Skin Health Alliance has awarded professional dermatological accreditation following review of the scientific dossier behind this product
- · Silicone Free

## **Applications**

- Good Grip, Durable Coating, Premium Performance
- Mechanical Equipment Maintenance and Repair
- Handling, Assembly and Sorting
- Finishing and Parts Inspection
- Industrial Applications
- **Precision Construction Jobs**



### **Technical Data**

| Color                | Green   |
|----------------------|---|
| Sizes Available      | XS-2XL  |
| Packaging            | Bulk Pack   |
| Packed               | 6 Dozen/Case                                      |
| Case Dimensions (cm) | 50.00 x 29.50 x 20.00                             |
| Case Weight (kg)     | 7.20  |
| Country of Origin    | Sri Lanka   |
| Liner Material       | Engineered Yarn                                   |
| Coating              | Nitrile   |
| Coating Color        | Black   |
| Coating Coverage     | Palm, Fingers & Knuckles                          |
| Grip                 | MicroFoam   |
| Gauge                | 15  |
| Cuff                 | Knit Wrist  |
| Impact Protection    |   |
| Construction         | Coated Seamless Knit,<br>Reinforced Thumb Crotch  |
| Certifications       | Silicone Free, Latex Free                         |
| Product Circularity  | Reusable / Launderable<br>Recycled via Terracycle |

#### **Performance Data**

| Cut Level                       | A2     |
|---------------------------------|--------|
| ANSI Abrasion Level             | 4      |
| ANSI Puncture Level             | 2      |
| ANSI Impact Level               |        |
| ANSI Contact Heat Level         |        |
| EN 388                          | 4341BX |
| ASTM F1358 Vertical Flame Level |        |
| EN 407                          |        |
|                                 |        |

KEY: Made from recycled or bio-based Launderable & Recyclable via TerraCycle®

