



ESD

### Technical Data

Color	White
Sizes Available	S-XL
Packaging	Case
Packed	14400/Case
Case Dimensions (cm)	48.26 x 25.40 x 30.48
Case Weight (kg)	8.62
Country of Origin	Viet Nam
Polymer	Nitrile
Grip	Smooth
Thickness	3.5 Mil
Powder	Powder Free
Construction	ESD Safe
Certifications	--
Product Circularity	--

### QRP® Qualatril®

Nitrile Latex-Free Vacuum Sealed Finger Cots  
ISO 5 (Class 100)

- Packaged for ISO 5 (Class 100) applications
- Average surface resistance of  $5 \times 10(9)$  ohms per square unit
- For use with Class II static sensitive devices (thresholds above 1000V)
- Unique, Stand-Up pouch for easy product identification
- ESD safe compliance to ANSI/ESD S20.20-2014
- For use with Class II static sensitive devices (thresholds above 1000V)
- RoHS compliant
- P3 Polar Process

### Performance Data

ISO Cleanroom	ISO 5 (Class 100)
Temperature Resistant	--
Static Control Property	Static Dissipative

**PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®**

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | [www.pipglobalsafety.com](http://www.pipglobalsafety.com)

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-06-29