



### Technical Data

Color	Black
Sizes Available	One Size
Packaging	Bagged Each
Packed	144/Case
Case Dimensions (cm)	70.00 x 38.00 x 35.00
Case Weight (kg)	9.00
Country of Origin	Taiwan
Lens	Mirror Plus Pro Polarized
Frame Style	Rimless
Lens Color	Red
Frame Fit	Universal
Lens Coating	Anti-Scratch
Bridge	Rubber
Temple	--
Diopter	--
Base Curve	8
Construction	--
Certifications	ANSI Z87.1, TAA Compliant
Product Circularity	--

### Site Boss

Enhanced Coverage Frameless Safety Glasses, with Black Temples, Fire Mirror Plus PRO Polarized High Contrast Lens, and Anti-Scratch Coating

- Mirror Plus PRO Polarized™ lens coating filters scattered sunlight from smooth surfaces, like water and snow, by controlling the angle at which light enters the lens for enhanced acuity and incredibly high contrast
- Modern and sporty frameless styling, with 60% larger lenses for more coverage
- AirFlex™ ultra-flexible temples provide a secure grip, even on larger head sizes
- Adjustable soft rubber nose pads designed for an ergonomic fit and all-day comfort
- Temple construction includes metal screws for durability
- ANSI Z87.1+ rated to protect the industrial athlete
- U6-rated UVA and UVB protection
- 8-base curved lens for a wide field of view
- Lens Coating: Anti-scratch is a hardcoat treatment that toughens the lens surface for a longer product life with fewer scratches.

**PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®**

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | [www.pipglobalsafety.com](http://www.pipglobalsafety.com)

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-07-06