



### Technical Data

|                      |                                                   |
|----------------------|---------------------------------------------------|
| Color                | White                                             |
| Sizes Available      | 12"-24"                                           |
| Packaging            | Bulk Pack                                         |
| Packed               | 144/Case                                          |
| Case Dimensions (cm) | 45.70 x 30.48 x 30.48                             |
| Case Weight (kg)     | 4.54                                              |
| Country of Origin    | United States                                     |
| Liner Material       | Antimicrobial, Pritex                             |
| Top of Arm           | Elastic Cuff                                      |
| Ply                  | Single-Ply                                        |
| Lining               | --                                                |
| Construction         | Blousy                                            |
| Certifications       | Silicone Free, TAA Compliant                      |
| Product Circularity  | Recycled via Terracycle<br>Reusable / Launderable |

### Kut Gard®

#### Single-Ply Pritex™ Blended Blousy Sleeve with Antimicrobial Fibers - Narrow Width

- Proprietary Pritex™ blend with antimicrobial fibers provides exceptional comfort and will not cause skin irritation
- Blousy construction offers a loose fit to reduce fatigue
- Raises the standards for performance sleeves offering an increase in overall performance and value compared to traditional Nylon and Nylon/Cotton blend sleeves
- Superior chemical resistance to acids, alkali, and organic solvents
- Stable against chlorine bleach
- Excellent abrasion and fatigue resistance

### Applications

- Sheet Metal Fabrication
- Paint Spraying
- Canning and Recycling
- Assembly
- Plastic Molding
- Food Processing

### Performance Data

|                                 |    |
|---------------------------------|----|
| Cut Level                       | A2 |
| ANSI Puncture Level             | -- |
| ANSI Contact Heat Level         | -- |
| ASTM F1358 Vertical Flame Level | -- |

### Care Instructions



Machine  
Wash



Water Temp  
55°C



Do Not  
Bleach



Tumble Dry

KEY: Made from recycled or bio-based Launderable Recyclable via TerraCycle®

**PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®**

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | [www.pipglobalsafety.com](http://www.pipglobalsafety.com)

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-07-02