



G-Tek® PolyKor®

Seamless Knit PolyKor® Blended Glove with Polyurethane Coated Flat Grip on Palm & Fingers

- Seamless construction offers increased comfort and breathability
- PolyKor® blended shell is lightweight and provides excellent dexterity, tactile sensitivity, and cut resistance
- Polyurethane coatings take on the surface properties of the glove liner providing a tactile grip in dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- Washable, resistant to chemicals, water, and ultraviolet light

Applications

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging



Technical Data

| | |
|----------------------|---|
| Color | Salt & Pepper |
| Sizes Available | -- |
| Packaging | Pair Bagged Retail Ready |
| Packed | -- |
| Case Dimensions (cm) | 38.00 x 27.50 x 24.00 |
| Case Weight (kg) | 5.70 |
| Country of Origin | Viet Nam |
| Liner Material | PolyKor |
| Coating | Polyurethane |
| Coating Color | Gray |
| Coating Coverage | Palm & Fingers |
| Grip | Flat |
| Gauge | 13 |
| Cuff | Knit Wrist |
| Impact Protection | -- |
| Construction | Coated Seamless Knit |
| Certifications | -- |
| Product Circularity | Reusable / Launderable Recycled via Terracycle |

Performance Data

| | |
|---------------------------------|-------|
| Cut Level | A3 |
| ANSI Abrasion Level | 6 |
| ANSI Puncture Level | 4 |
| ANSI Impact Level | -- |
| ANSI Contact Heat Level | -- |
| EN 388 | 4X43C |
| ASTM F1358 Vertical Flame Level | -- |
| EN 407 | -- |

Care Instructions

