

# SPECIFICATION SHEET

STYLE: 19-D326



## G-Tek® ECO Series™

Seamless Knit Dyneema® Phoenix Blended Glove with Polyurethane Coated Flat Grip on Palm & **Fingers** 

- · Seamless construction offers increased comfort and breathability
- Spun Dyneema® Phoenix & Spandex shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Bio-Based Dyneema fiber provides same performance & protection, while providing lower carbon footprint
- Dyneema® bio-based fibers equates to 450g of CO2 emissions reduction per pair when compared to traditional Dyneema® fibers
- Polyurethane coatings take on the surface properties of the glove liner providing a tactile grip in dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Knit Wrist helps prevent dirt and debris from entering the glove

## **Applications**

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging













### **Technical Data**

| Color                | Gray  |
|----------------------|---|
| Sizes Available      |   |
| Packaging            | Pair Bagged Retail Ready  |
| Packed               |   |
| Case Dimensions (cm) | 30.00 x 32.00 x 36.00   |
| Case Weight (kg)     | 4.00  |
| Country of Origin    | Viet Nam  |
| Liner Material       | Dyneema Phoenix   |
| Coating              | Polyurethane  |
| Coating Color        | Black   |
| Coating Coverage     | Palm & Fingers  |
| Grip                 | Flat  |
| Gauge                | 13  |
| Cuff                 | Knit Wrist  |
| Impact Protection    |   |
| Construction         | Coated Seamless Knit  |
| Certifications       |   |
| Product Circularity  | Reusable / Launderable Recycled via Terracycle Contains Bio-Based Materials |

### **Performance Data**

| Cut Level                       | A3     |
|---------------------------------|--------|
| ANSI Abrasion Level             | 5      |
| ANSI Puncture Level             | 3      |
| ANSI Impact Level               |        |
| ANSI Contact Heat Level         |        |
| EN 388                          | 4X42CX |
| ASTM F1358 Vertical Flame Level |        |
| EN 407                          |        |

KEY: Made from recycled or bio-based Launderable & Recyclable via TerraCycle®